
TECHNICAL DATA SHEET

DISAFOAM SB 735 S/EX

DESCRIPTION

DISAFOAM SB 735 S/EX is a modified polysiloxane-based defoamer with high performance that behaves as an efficient foam-controlling agent in solvent-borne systems providing good surface leveling even in high solids paint formulations.

DISAFOAM SB 735 S/EX is indicated for epoxy, alkyd PU and acrylic PU paints and enamels.

PHYSICAL ASPECT

Appearance..... Transparent liquid
Colour..... Colourless
Odour..... Characteristic
Density..... 0,91 - 0,93 g/cm³
Non-volatile content (%)..... 14,0 - 16,0

APPLICATION

- Architectural, industrial and automotive synthetic enamels in solvent;
- Epoxy and PU paints and enamels in solvent;
- Synthetic enamels for metal mechanics in solvent;
- Paints and enamels for the furniture and wood industries in solvent;
- Enamels and special paints in solvent.

HOW TO USE

Able to be added at the end of paint formulations without causing surface defects. The dosages can range from 0.05% to 0.5% of the total formulation.

HANDLING

DISAFOAM SB 735 S/EX should be handled with security glasses, gloves and preferentially with PVC apron. It should be handled similarly to solvent-borne resins.

PACKAGING AND STORING

DISAFOAM SB 735 S/EX is supplied in either 18kg or 45kg jerricans, or even in 180kg metal drums with fixed cover.

DISAFOAM SB 735 S/EX can be stored for a period of 24 months. It should be stored under the shade and airy places.

DISAMTEX LTDA

2000 Rudolfo Walter Rd . 89068-239 - Blumenau (SC) - Brazil

(55-47) 3337.3600 - disamtex.com.br